

Tri Auto ZX2+



EO Endo.
Optimized.

Thinking ahead. Focused on life.

Beyond Ingenuity

Intelligent Endodontic Motor



Patency and Glide Path Have Never Been Easier

Tri Auto ZX2+ is equipped with a new generation reciprocating drive, OGP2, that greatly reduces the chance of a file breaking in the canal. This innovative motor can be used for patency, glide path, and shaping, allowing you to finish treatment safely and in less time. Additionally, with no limits on file size or cutting direction, your current file system is compatible. The future of endodontic treatment is here...Tri Auto ZX2+.

EO Endo.
Optimized.



Next Level Reciprocation


Introducing OGP2

OGP2 (Optimum Glide Path 2) Reduces the Chance of File Breakage

OGP2 dramatically reduces the chance of breaking files due to its new and innovative reciprocating motion. Even patency using a #10 scout file is possible. Notoriously difficult patency by hand filing can now be achieved by endo motor!

Rotation

Its intelligent motion reduces file binding and, when it does occur, helps prevent the file from breaking in the canal.



Maintains the Root Canal Shape

Even with curved or narrow root canals, OGP2 allows you to provide treatment that maintains the original root canal shape.







Preoperative

Postoperative

Handles Patency, Glide Path, and Shaping Using Just One Mode

From a #10 scout file, to the widest size available, the Tri Auto ZX2+ handles any CW/CCW file all in one mode. Patency, glide path, and shaping can all be performed with OGP2, allowing you to focus on treatment rather than settings.

Mode				
Sequence	 Coronal flaring	 Patency (Scouting)	 Glide Path	 Shaping
File example	#25 / 08 or #35 / 08	#10 / 02	#15 / 04	#20 / 04 - #40 / 04* #20 / 06 - #40 / 06*

Available  and  files.

* Decide on the final file size according to the shape of the root canal.

OTR Mode Now Supports Both Reciprocation and Rotary Files

OTR (Optimum Torque Reverse) Offers Enhanced Safety and Performance

OTR technology offers superior safety while efficiently preparing the canal. Continuous rotation is maintained until the file encounters resistance in the curved and difficult part of the canal. Depending on the file load, the motor alternates between forward and reverse rotation with great sensitivity to prevent jamming and file breakage. OTR mode now supports reciprocation files in addition to rotary files. Modification of the cutting angle can be made to suit your needs.

OTR CW mode

Cutting Direction: Clockwise (CW)

Non-Cutting Direction: Counterclockwise (CCW)

NEW! OTR CCW mode

Cutting Direction: Counterclockwise (CCW)

Non-Cutting Direction: Clockwise (CW)

Suitable for Reciprocation files




World-leading apex location Built Right in

Root ZX Technology

Capable of high-precision measurement without being affected by dry or wet canals, the integrated apex locator allows you to perform treatment while continuously monitoring the position of the file.

The Tri Auto ZX2+ also provides multiple safety features utilizing Root ZX's proven accuracy to stop rotation and prevent over-instrumentation of the root canal.


Since 1992



Apical Slow Down

Activated when the OGP2 mode is operating, Apical Slow Down reduces the rotation speed of the file as it approaches the apex. This function allows you to provide treatment that simulates the feel of hand filing while also reducing the chance of file breakage.

Slow Down →



Cases

Case 1

Curved root canal (left maxillary first molar)



Preoperative



Postoperative

Mesiobuccal (MB) and distobuccal (DB) roots of #26 are constricted, and only a few millimeters of patency was achieved with hand files. Then a mechanical glide path using OGP2 was established. OGP2 could obtain glide path preparation without any difficulties such as broken files or ledge formation to constricted canals even to DB, which has severe constriction and S-shape curvature. Total time to complete mechanical glide path using OGP2 was 5 minutes.

Case 2

Sclerosed root canal (right maxillary first molar)



Preoperative




Postoperative

The radiographic images highlight that a root canal system was still present. The detection of the root canal orifice and root canal preparation were difficult due to the presence of mineralized tissue. The OGP2 mode contributed to attaining patency and glide path on 4 roots, including the second mesiobuccal (MB2) root canal. Subsequently, root canal preparation was completed using OTR mode on the device. All procedures ranging from the patency of the 4 root canals to the final root preparation were carried out in approximately 7 minutes.

Case 3

Patency abandoned (left maxillary second molar)



Preoperative



Postoperative

Retreatment case of #37, root canal patency was not obtained during the past treatment. After root canal orifices are specified, patency was obtained using OGP2. Both mesiobuccal (MB) and distobuccal (DB) canals have S-shape curvature, and especially MB was challenging. If only with hand instruments, treatment time for MB would be extremely long. By using OGP2, total time needed for glide path preparation was 14 minutes in total; 6 minutes for MB, 5 minutes for DB and 3 minutes for palatal canal.

Clinical images and comments are provided by: Dr. Toshihiro Ushikubo
Dr. Motoki Okamoto
Dr. Tai Gega

*The images shown here represent examples of post surgery progress at the clinic that provided the photos.

*A pre-sales clinical survey conducted by J.MORITA MFG.CORP. showed that of the dentists that used OGP2, 77% used it for patency and 86% used it for glide path.

One Motor Can Do All This?
Apex Location, Patency, Glide Path, Shaping
All In One.



Various Modes

Display				
Mode	EMR	CONT-CW	Optimum Glide Path 2	Optimum Glide Path 2
Usage	Apex location	Coronal flaring	Patency (Scouting) Glide path Shaping (Flash Bar Position=0.5)	Patency (Scouting) Glide Path Shaping (Flash Bar Position=1.0)
	Optimum Torque Reverse (CW)	Optimum Torque Reverse (CCW)	CONT-CW	CONT-CCW
	Optimum Torque Reverse (CCW)			
Shaping (for CW files)	Shaping (for CCW files)	Root canal irrigation with irrigation files	Inject intraoral medicament	Ledge bypass

Specifications

Name: Tri Auto ZX2
Model: TR-ZX2
Type: PLUS
Manufacturer: J. MORITA MFG. CORP.

Functions: Apex location
OGP2 (Optimum Glide Path2)
OGP (Optimum Glide Path)
OTR (Optimum Torque Reverse)
OAS (Optimum Apical Stop)
OAS2 (Optimum Apical Stop2)
Auto Start / Stop, Auto Apical Reverse
Auto Apical Stop, Apical Slow Down
Torque Slow Down, Apical Torque Down
Auto Torque Reverse

Accessories: Tester, LS OIL
Power Plugs (one each of 4 types)
Probe Cord (0.75 m)
File Holder, Contrary Electrodes
HP Protective Sleeve Type A

Options: Handpiece Holder, Long File Holder
External File Electrode (with cap)
Probe Cord (1.8 m)

Handpiece

Free Running Operation


Speed: 100 – 1000 rpm
Torque: 4 Ncm or more
Battery: Lithium-ion battery (DC 3.7 V)
Weight: Approx. 140 g (including battery and contra angle)

Battery Charger

Rated Input Voltage: DC 5 V
Rated Input Current: 2.4 A
Weight: Approx. 280 g
(AC adapter not included)

AC Adapter

Rated Input Voltage: AC100 - 240 V
Rated Input Frequency: 47 - 63 Hz
Rated Input Current: 0.4 A





Development and Manufacturing

J. MORITA MFG. CORP.

680 Higashihama Minami-cho, Fushimi-ku,
Kyoto 612-8533, Japan
T +81. (0)75. 611 2141, F +81. (0)75. 622 4595

Morita Global Website
www.morita.com

Distribution

J. MORITA CORP.

3-33-18 Tarumi-cho, Suita-shi, Osaka 564-8650, Japan
T +81. (0)6. 6380 1521, F +81. (0)6. 6380 0585

J. MORITA USA, INC.

9 Mason, Irvine CA 92618, USA
T +1. 949. 581 9600, F +1. 949. 581 8811

J. MORITA EUROPE GMBH

Justus-von-Liebig-Strasse 27b, 63128 Dietzenbach, Germany
T +49. (0)6074. 836 0, F +49. (0)6074. 836 299

MORITA DENTAL ASIA PTE. LTD.

150 Kampong Ampat, #06-01A KA Centre, Singapore 368324
T +65. 6779. 4795, F +65. 6777. 2279

J. MORITA CORP. AUSTRALIA & NEW ZEALAND

Suite 2.05, 247 Coward Street, Mascot NSW 2020, Australia
T +61. (0)2. 9667 3555, F +61. (0)2. 9667 3577

J. MORITA CORP. MIDDLE EAST

4 Tag Al Roasaa, Apartment 902, Saba Pacha 21311 Alexandria, Egypt
T +20. (0)3. 58 222 94, F +20. (0)3. 58 222 96

J. MORITA CORP. INDIA

Filix Office No.908, L.B.S. Marg, Opp. Asian Paints, Bhandup (West), Mumbai 400078, India
T +91-22-2595-3482

J. MORITA MFG. CORP. INDONESIA

28F, DBS Bank Tower, Jl. Prof. Dr. Satrio Kav. 3-5, Jakarta 12940, Indonesia
T +62-21-2988-8332, F + 62-21-2988-8201

SIAMDENT CO., LTD.

71/10 Mu 5, Thakham, Bangpakong, Chachuengsao 24130, Thailand
T +66. 38. 573042, F +66. 38. 573043
www.siamdent.com

Diagnostic and Imaging Equipment

Treatment Units

Handpieces and Instruments

Endodontic System

Laser Equipment

Laboratory Devices

Educational and Training Systems

Auxiliaries

Subject to technical changes and errors.

"Endo. Optimized." is a trademark that represents the inclusion of proprietary technology developed by J. MORITA MFG. CORP for Endodontic devices.
It does not imply any claims regarding efficacy or device performance.

Pub. No. ES616-0875-3-EN-4